

POLYPROPYLENE RESIN COMPOSITION

Publication number: JP62072739

Publication date: 1987-04-03

Inventor: MINO TATSUYUKI; KOYAMA TERUHISA; IKEZAWA YUJI

Applicant: SUMITOMO CHEMICAL CO

Classification:

- international: C08L23/26; C08K3/34; C08L7/00; C08L21/00;
C08L23/00; C08L23/10; C08L51/00; C08L51/02;
C08L53/00; C08L77/00; C08L101/00; C08K3/00;
C08L7/00; C08L21/00; C08L23/00; C08L51/00;
C08L53/00; C08L77/00; C08L101/00; (IPC1-7):
C08K3/34; C08L21/00; C08L23/26

- European:

Application number: JP19850212883 19850926

Priority number(s): JP19850212883 19850926

Report a data error here

Abstract of JP62072739

PURPOSE:To obtain the titled composition having well-balanced rigidity and impact strength and excellent heat-resistance and appearance of molded article and suitable as automobile parts, etc., by compounding a specific modified polyolefin resin with a rubbery substance and a specific amount of mica having specific particle diameter and particle diameter distribution. **CONSTITUTION:**The objective composition can be produced by compounding (A) 40-97(wt)% polyolefin resin composition consisting of (A1) a polypropylene resin having a melt index of 0.1-100 (e.g. polypropylene) and (A2) modified polyolefin resin grafted with 0.01-5% unsaturated carboxylic acid (anhydride) (e.g. maleic anhydride) (the ratio of the component A2 is $\geq 2\%$, preferably $\geq 5\%$) with (B) 0-20% rubber substance (e.g. ethylene-propylene copolymer rubber) and (C) 3-50% mica (e.g. white mica) having an average particle diameter of 0.5-4.5 μ m wherein the fractions having diameter of $\leq 10\mu$, $\leq 5\mu$ and $\leq 1\mu$ are $\geq 95\%$, $\geq 60\%$ and 10-80%, respectively.

Data supplied from the esp@cenet database - Worldwide